



Kimono Sleeve Crop Top



**INSTRUCTION
BOOKLET**

Table of Contents

- 3 What do I need to start sewing?
- 4 Printing instructions
- 6 Size chart
- 7 Patterns
- 8 Sewing instructions
- 12 Styling options
- 13 Glossary



COPYRIGHT - All rights reserved.
© 2023 Patterns For Less


Written permission is required to copy and/or distribute copies of this document, whether or not it is for profit. Photocopying, digitizing or copying this document to share is strictly prohibited.

Help support the development of Patterns For Less sewing patterns by checking out the new arrivals.

For inquiries, questions, drop me a message on
IG: PatternsForLess
info@patternsforless.com

Sign up to my email list for discounts and exciting store updates!
PatternsForLess.com

What do I need to start sewing?



Sewing machine
Overlock/Serger
Pattern printout
Sewing thread
Measuring tape
Water erasable pen/Chalks
Scissors
Ruler
Pins

1 yard 100% polyester fabric

Fabric Recommendations: Non-stretch woven fabric, 100% polyester, viscose, cotton, gauze, crepe de chine.

Printing Instructions

Let's print out the pattern!


The sewing pattern comes with 3 different printing options! The US Letter and A4 print is a tile version PDF that you can print out at home. The A0 version is used by a printshop to print on a single sheet of paper and saves time taping the separate pages together.

Additionally, you can use view mode to only select/print the size you are working on. Each pattern file is designed with layers of different sizes. There is an option to print only your size or all sizes based on your preference. Open the file in Adobe Acrobat and keep in legend layer.


If you print at home, then you need to trim each sheet by cutting off the top and excess margin. Tape each page together by row, and then attach the rows together. Use the diamond marks to align everything!

Always make sure to print on 100% scale.
(Do not 'fit to page' or reduce the size!)


There is a test square on the first page of the pattern.
Use as a scale to check if the dimensions are 5x5cm and/or 2x2".



A4



US Letter



Size Chart


inches

SIZE	BUST	WAIST	HIP
XS	30	25	36
S	33	27	38
M	36	29	40
L	39	31	42
XL	41	33	44
XXL	44	35	46
XXXL	47	37	48

centimeters

SIZE	BUST	WAIST	HIP
XS	76	63	91
S	84	68	96
M	91	74	102
L	99	79	107
XL	104	84	112
XXL	112	89	117
XXXL	119	94	122

Patterns




Kimono sleeve front tie crop top pattern pieces include:

- A- Front Top, cut 2
- B- Back Top, cut 1 on fold
- C- Front Tie, cut 2 on fold
- D- Neck Binding, cut 1 (on bias) on fold



$\frac{3}{8}$ " or 1cm seam allowance is already included unless indicated on the pattern or instruction book.

Sewing Instructions




Step 1- Place both left and right side of Front Top (A) and Back Top (B) facing right side together and pin along the shoulder and underarm.

Step 2- Stitch $\frac{3}{8}$ " or 1cm width along the pinned area and finish the raw edges with overlock stitch.




Step 3- Press the shoulder, side, and underarm seams facing towards the Back Top.

KIMONO SLEEVE CROP TOP




Step 4- Prepare the Neck Binding by cutting the fabric on bias and press to create a folded line to make it easy to sew (refer to Sewing Glossary section). Put right side of Neck Binding (D) around the neckline on the right side of Front Top and Back Top. Then, pin and sew $\frac{1}{4}$ " or 0.6cm along the crease all around the pinned neckline.


Step 5- Press the allowance towards the binding. Fold the binding over so that half is on the wrong side of the fabric.




Step 6- Press the binding toward the wrong side of the fabric. Then, double fold the binding and edge topstitch along the edge of the binding. Ensure that the raw edge of the bias tape is folded under so it is not visible.




KIMONO SLEEVE CROP TOP




Step 7- Before attaching the front tie, double fold the hemline of Front Top and Back Top with $\frac{1}{4}$ " or 0.6cm width stitching. Give a nice press.




Step 8- Prepare the Front Tie (C) by folding right side facing each other lengthwise and pin. For more assistance, press the folded line.



Step 9- Sew $\frac{1}{4}$ " or 0.6cm width seam allowance along the cut edge lengthwise and leave one short side open. Trim the corners so it becomes easy to flip and results in sharp corners. Use loop turner, safety pin or straw and long stick to flip the strap inside out and give a nice press.





Step 10- Attach the cut ends of Front Tie to the notches of Front Top and sew $\frac{1}{4}$ " or 0.6cm width. Overlock both the raw edges and press the seam towards the Front Top, then edge topstitch $\frac{1}{4}$ " or 0.6cm width.




Step 11- Double fold the sleeve opening with $\frac{1}{4}$ " or 0.6cm width stitching around and press to complete.


Styling Options



If the front tie is too revealing or you already have a similar look, try to wear the back as front and have the tie on the backside.




The front tie is long enough to wrap around your high waist to make a wrap crop top and finish tying in the back.





Sewing Glossary

Back Stitch




When you start a new seam or finish the seam, always backstitch by hitting the reverse button on your sewing machine. Back stitching consists of 3-4 stitches to lock the stitching and prevent unraveling.

Bias Tape



Bias tape is widely used in neckline, spaghetti strap, and other garment finishings. Prepare the bias strap by cutting in half diagonally to give a nice stretch. When needing to make a long continuous bias tape, sew the diagonal pieces together as long as you need.


Buttonholes



There are various styles of buttonholes you can create with your sewing machine. For cleaner look, add interfacing and sew over the buttonhole more than once to create nice tight holes.


Use a buttonhole foot by inserting the button in the back of the foot, and snap the foot into place. Pull the button hole lever down, and select the buttonhole stitch on your machine. Press the pedal and stitch away, your machine will automatically go through the steps to make an accurate buttonhole.

Edge Stitch



Edge stitches are typically used to decorate or emphasize the original seam line. To achieve clean edge stitch, use a special footer to sew close to the edges without gliding off. Sew slowly to control the fabric.


Flat Felled Seam



Flat felled seam or jeans seams is a great way to sew heavy duty fabric or bottoms to strengthen the garment.

Sew the fabric right sides facing each other. Trim one of the seam allowances in half. Turn the raw edge under and fold over to hide the half cut edge. Topstitch down the enclosed seam allowance.


French Seam



When sewing silk or chiffon with delicate fabrication, French seams are a great way to achieve an excellent quality finish.


Place wrong sides of fabric facing each other and sew $\frac{1}{4}$ " or 0.6cm. Press the seam and fold the fabric along the seam line. Enclose the seam by stitching $\frac{1}{4}$ " or 0.6cm from the folded edge.

Hand Basting




Basting or running stitches are simple hand stitches to use instead of pinning or gathering. Alternatively, you can increase the stitch length and loosen tension on your sewing machine to create a basting look.

Open Seam



Open seams are a technique used to make the seams clean and flat. It can be used for CF, CB, or side seams. Overlock both raw edges first, and then stitch the 2 pieces together to iron the seam open.


Overlock



Overlock stitches help to bind raw cut edges to prevent from fraying. This technique is mostly accomplished by overlock machine, serger, or your home sewing machine with overlock stitch setting.

Overlock machines have 2 to 3 needles and 2 top threads and lower threads to braid and stitch, which results in a variation of blanket stitch. The knife blade cuts the fabric edge to give a clean overlock stitch.


Pivoting



Use the pivoting method when sewing corners or at an angle such as pocket corners, tip of collars, v-neckline, etc.


Execute the technique by leaving the needle in the fabric, lift the footer, and then turn the fabric as much as you need. Continue to sew by lowering the footer again, then stitch in the new direction.

Pressing



Steam and iron with pressure after every stitch you make in the garment. Pressing helps to relax the threads and finish the seams cleanly. Be aware to avoid extreme steam on natural fabrics such as cotton and linen due to the risk in shrinkage.


Right side - Wrong side



All fabrics have a right side and wrong side. The right side is mostly worn visibly to the outside whereas the wrong side should be on the inside of the garment. Some fabrics are easy to identify the right or wrong side by sheen or texture, but some might look identical both right and wrong side.

To find out the right and wrong side of the fabric, look for little pinholes along the selvage. The clean side of the holes is the right side.


Seam Allowance



The seam allowance or SA is the extra fabric next to the stitch line all around each pattern piece. The additional space allows us to sew everything together.


Depending on the seams and styles, the seam allowance is usually ($\frac{1}{4}"$, $\frac{3}{8}"$, $\frac{1}{2}"$) or (.6cm, 1cm or 1.2cm) width. Always refer to the pattern and instruction booklet for accurate seam allowance amount.

Topstitch



The purpose of top stitches are to add strength to the garment. Iron the seam allowance to the side. Straight stitch $\frac{1}{8}$ " or 0.3cm, or $\frac{1}{4}$ " or 0.6cm away from the original seam to sew the right side and seam allowance together.

Twin Needle



Twin needles are used in knit casual or sportswear for clean finishing without needing a double fold hemming method. The 2 top threads and 1 bobbin thread create parallel topstitch on the right side of the fabric and zigzag stitch on the wrong side of the fabric.